



YAW-YEW

YAW-YEW RUBBER 耀裕橡膠

Connecting To Your Wish

AS568 O-RING STANDARD SIZE LIST SERIES


How We Make Your Products Perfect 至臻至美 · 出眾首選





AS568 O-RING

STANDARD SIZE LIST SERIES




#AS568	Nominal Size		ACTUAL SIZE							
	Inches 內徑(I.D.)	線徑(W)	Inches 內徑(I.D.) ± 線徑(W) ±				Millimeters 內徑(I.D.) ± 線徑(W) ±			
-001	1/32	1/32	0.029	0.004	0.040	0.003	0.74	0.11	1.02	0.07
-002	3/64	3/64	0.042	0.004	0.050	0.003	1.07	0.11	1.27	0.07
-003	1/16	1/16	0.056	0.004	0.060	0.003	1.42	0.11	1.53	0.07
-004	5/64	1/16	0.070	0.005	0.070	0.003	1.78	0.12	1.78	0.08
-005	7/64	1/16	0.101	0.005	0.070	0.003	2.57	0.12	1.78	0.08
-006	1/8	1/16	0.114	0.005	0.070	0.003	2.90	0.12	1.78	0.08
-007	5/32	1/16	0.145	0.005	0.070	0.003	3.69	0.12	1.78	0.08
-008	3/16	1/16	0.176	0.005	0.070	0.003	4.47	0.12	1.78	0.08
-009	7/32	1/16	0.208	0.005	0.070	0.003	5.29	0.12	1.78	0.08
-010	1/4	1/16	0.239	0.005	0.070	0.003	6.07	0.12	1.78	0.08
-011	5/16	1/16	0.301	0.005	0.070	0.003	7.65	0.12	1.78	0.08
-012	3/8	1/16	0.364	0.005	0.070	0.003	9.25	0.12	1.78	0.08
-013	7/16	1/16	0.426	0.005	0.070	0.003	10.82	0.12	1.78	0.08
-014	1/2	1/16	0.489	0.005	0.070	0.003	12.42	0.12	1.78	0.08
-015	9/16	1/16	0.551	0.005	0.070	0.003	14.00	0.12	1.78	0.08
-016	5/8	1/16	0.614	0.005	0.070	0.003	15.60	0.12	1.78	0.08
-017	11/16	1/16	0.676	0.005	0.070	0.003	17.17	0.12	1.78	0.08
-018	3/4	1/16	0.739	0.005	0.070	0.003	18.77	0.12	1.78	0.08
-019	13/16	1/16	0.801	0.006	0.070	0.003	20.35	0.15	1.78	0.08
-020	1	1/16	0.864	0.006	0.070	0.003	21.95	0.15	1.78	0.08
-021	15/16	1/16	0.926	0.006	0.070	0.003	23.52	0.15	1.78	0.08
-022	1	1/16	0.989	0.006	0.070	0.003	25.12	0.15	1.78	0.08
-023	1_1/16	1/16	1.051	0.006	0.070	0.003	26.70	0.15	1.78	0.08
-024	1_1/8	1/16	1.114	0.006	0.070	0.003	28.30	0.15	1.78	0.08
-025	1_3/16	1/16	1.176	0.006	0.070	0.003	29.87	0.15	1.78	0.08

更多詳細規格資訊，請至耀裕官網查詢 For more information, please visit our website.



AS568 O-RING

STANDARD SIZE LIST SERIES




#AS568	Nominal Size		ACTUAL SIZE							
	Inches 內徑(I.D.)	線徑(W)	Inches 內徑(I.D.) ± 線徑(W) ±				Millimeters 內徑(I.D.) ± 線徑(W) ±			
-026	1_1/4	1/16	1.239	0.006	0.070	0.003	31.47	0.15	1.78	0.08
-027	1_5/16	1/16	1.301	0.006	0.070	0.003	33.05	0.15	1.78	0.08
-028	1_3/8	1/16	1.364	0.006	0.070	0.003	34.65	0.15	1.78	0.08
-029	1_1/2	1/16	1.489	0.010	0.070	0.003	37.82	0.25	1.78	0.08
-030	1_5/8	1/16	1.614	0.010	0.070	0.003	41.00	0.25	1.78	0.08
-031	1_3/4	1/16	1.739	0.010	0.070	0.003	44.17	0.25	1.78	0.08
-032	1_7/8	1/16	1.764	0.010	0.070	0.003	47.35	0.25	1.78	0.08
-033	2	1/16	1.998	0.010	0.070	0.003	50.52	0.25	1.78	0.08
-034	2_1/8	1/16	2.114	0.010	0.070	0.003	53.70	0.25	1.78	0.08
-035	2_1/4	1/16	2.239	0.010	0.070	0.003	56.87	0.25	1.78	0.08
-036	2_3/8	1/16	2.364	0.010	0.070	0.003	60.04	0.25	1.78	0.08
-037	2_1/2	1/16	2.489	0.010	0.070	0.003	63.22	0.25	1.78	0.08
-038	2_5/8	1/16	2.614	0.010	0.070	0.003	66.40	0.25	1.78	0.08
-039	2_3/4	1/16	2.739	0.015	0.070	0.003	69.57	0.38	1.78	0.08
-040	2_7/8	1/16	2.864	0.015	0.070	0.003	72.75	0.38	1.78	0.08
-041	3	1/16	2.989	0.015	0.070	0.003	75.92	0.38	1.78	0.08
-042	3_1/4	1/16	3.239	0.015	0.070	0.003	82.27	0.38	1.78	0.08
-043	3_1/2	1/16	3.489	0.015	0.070	0.003	88.62	0.38	1.78	0.08
-044	3_3/4	1/16	3.739	0.015	0.070	0.003	94.97	0.38	1.78	0.08
-045	4	1/16	3.989	0.015	0.070	0.003	101.32	0.38	1.78	0.08
-046	4_1/4	1/16	4.239	0.015	0.070	0.003	107.67	0.38	1.78	0.08
-047	4_1/2	1/16	4.489	0.015	0.070	0.003	114.02	0.38	1.78	0.08
-048	4_3/4	1/16	4.739	0.015	0.070	0.003	120.37	0.38	1.78	0.08
-049	5	1/16	4.989	0.023	0.070	0.003	126.72	0.58	1.78	0.08
-050	5_1/4	1/16	5.239	0.023	0.070	0.003	133.07	0.58	1.78	0.08

Size - 051 through - 101 not assigned (尺寸大小51-101未分配)



AS568 O-RING

STANDARD SIZE LIST SERIES




#AS568	Nominal Size		ACTUAL SIZE							
	Inches 內徑(I.D.)	線徑(W)	Inches 內徑(I.D.) ± 線徑(W) ±				Millimeters 內徑(I.D.) ± 線徑(W) ±			
-102	1/16	3/32	0.049	0.005	0.103	0.003	1.24	0.12	2.62	0.08
-103	3/32	3/32	0.081	0.005	0.103	0.003	2.05	0.12	2.62	0.08
-104	1/8	3/32	0.112	0.005	0.103	0.003	2.84	0.12	2.62	0.08
-105	5/32	3/32	0.143	0.005	0.103	0.003	3.63	0.12	2.62	0.08
-106	3/16	3/32	0.174	0.005	0.103	0.003	4.42	0.12	2.62	0.08
-107	7/32	3/32	0.206	0.005	0.103	0.003	5.23	0.12	2.62	0.08
-108	1/4	3/32	0.237	0.005	0.103	0.003	6.02	0.12	2.62	0.08
-109	5/16	3/32	0.299	0.005	0.103	0.003	7.60	0.12	2.62	0.08
-110	3/8	3/32	0.362	0.005	0.103	0.003	9.19	0.12	2.62	0.08
-111	7/16	3/32	0.424	0.005	0.103	0.003	10.77	0.12	2.62	0.08
-112	1/2	3/32	0.487	0.005	0.103	0.003	12.37	0.12	2.62	0.08
-113	9/16	3/32	0.549	0.005	0.103	0.003	13.95	0.12	2.62	0.08
-114	5/8	3/32	0.612	0.005	0.103	0.003	15.54	0.12	2.62	0.08
-115	11/16	3/32	0.674	0.005	0.103	0.003	17.12	0.12	2.62	0.08
-116	3/4	3/32	0.737	0.005	0.103	0.003	18.72	0.12	2.62	0.08
-117	13/16	3/32	0.799	0.006	0.103	0.003	20.29	0.15	2.62	0.08
-118	7/8	3/32	0.862	0.006	0.103	0.003	21.90	0.15	2.62	0.08
-119	15/16	3/32	0.924	0.006	0.103	0.003	23.47	0.15	2.62	0.08
-120	1	3/32	0.987	0.006	0.103	0.003	25.07	0.15	2.62	0.08
-121	1_1/16	3/32	1.049	0.006	0.103	0.003	26.65	0.15	2.62	0.08
-122	1_1/8	3/32	1.112	0.006	0.103	0.003	28.25	0.15	2.62	0.08
-123	1_3/16	3/32	1.174	0.006	0.103	0.003	29.82	0.15	2.62	0.08
-124	1_1/4	3/32	1.237	0.006	0.103	0.003	31.42	0.15	2.62	0.08
-125	1_5/16	3/32	1.299	0.006	0.103	0.003	33.00	0.15	2.62	0.08
-126	1_3/8	3/32	1.362	0.006	0.103	0.003	36.60	0.15	2.62	0.08

更多詳細規格資訊，請至耀裕官網查詢 For more information, please visit our website.



AS568 O-RING

STANDARD SIZE LIST SERIES




#AS568	Nominal Size	ACTUAL SIZE								
		Inches		Inches		Millimeters				
內徑(I.D.)	線徑(W)	內徑(I.D.)	±	線徑(W)	±	內徑(I.D.)	±	線徑(W)	±	
-127	1_7/16	3/32	1.424	0.006	0.103	0.003	36.17	0.15	2.62	0.08
-128	1_1/2	3/32	1.487	0.006	0.103	0.003	37.77	0.15	2.62	0.08
-129	1_9/16	3/32	1.549	0.010	0.103	0.003	39.35	0.25	2.62	0.08
-130	1_5/8	3/32	1.612	0.010	0.103	0.003	40.95	0.25	2.62	0.08
-131	1_11/16	3/32	1.674	0.010	0.103	0.003	42.52	0.25	2.62	0.08
-132	1_3/4	3/32	1.737	0.010	0.103	0.003	44.12	0.25	2.62	0.08
-133	1_13/16	3/32	1.799	0.010	0.103	0.003	45.70	0.25	2.62	0.08
-134	1_7/8	3/32	1.862	0.010	0.103	0.003	47.30	0.25	2.62	0.08
-135	1_15/16	3/32	1.925	0.010	0.103	0.003	48.90	0.25	2.62	0.08
-136	2	3/32	1.987	0.010	0.103	0.003	50.47	0.25	2.62	0.08
-137	2_1/16	3/32	2.050	0.010	0.103	0.003	52.07	0.25	2.62	0.08
-138	2_1/8	3/32	2.112	0.010	0.103	0.003	53.65	0.25	2.62	0.08
-139	2_3/16	3/32	2.175	0.010	0.103	0.003	55.25	0.25	2.62	0.08
-140	2_1/4	3/32	2.237	0.010	0.103	0.003	56.82	0.25	2.62	0.08
-141	2_5/16	3/32	2.300	0.010	0.103	0.003	58.42	0.25	2.62	0.08
-142	2_3/8	3/32	2.362	0.010	0.103	0.003	60.00	0.25	2.62	0.08
-143	2_7/16	3/32	2.425	0.010	0.103	0.003	61.60	0.25	2.62	0.08
-144	2_1/2	3/32	2.487	0.010	0.103	0.003	63.17	0.25	2.62	0.08
-145	2_9/16	3/32	2.550	0.010	0.103	0.003	64.77	0.25	2.62	0.08
-146	2_5/8	3/32	2.612	0.010	0.103	0.003	66.35	0.25	2.62	0.08
-147	2_11/16	3/32	2.675	0.015	0.103	0.003	67.95	0.38	2.62	0.08
-148	2_3/4	3/32	2.737	0.015	0.103	0.003	69.52	0.38	2.62	0.08
-149	2_13/16	3/32	2.800	0.015	0.103	0.003	71.12	0.38	2.62	0.08
-150	2_7/8	3/32	2.862	0.015	0.103	0.003	72.70	0.38	2.62	0.08

更多詳細規格資訊，請至耀裕官網查詢 For more information, please visit our website.



AS568 O-RING

STANDARD SIZE LIST SERIES




#AS568	Nominal Size	ACTUAL SIZE								
		Inches		Inches				Millimeters		
內徑(I.D.)	線徑(W)	內徑(I.D.)	±	線徑(W)	±	內徑(I.D.)	±	線徑(W)	±	
-151	3	3/32	2.987	0.015	0.103	0.003	75.87	0.38	2.62	0.08
-152	3_1/4	3/32	3.237	0.015	0.103	0.003	82.22	0.38	2.62	0.08
-153	3_1/2	3/32	3.487	0.015	0.103	0.003	88.57	0.38	2.62	0.08
-154	3_3/4	3/32	3.737	0.015	0.103	0.003	94.92	0.38	2.62	0.08
-155	4	3/32	3.987	0.015	0.103	0.003	101.27	0.38	2.62	0.08
-156	4_1/4	3/32	4.237	0.015	0.103	0.003	107.62	0.38	2.62	0.08
-157	4_1/2	3/32	4.487	0.015	0.103	0.003	113.97	0.38	2.62	0.08
-158	4_3/4	3/32	4.737	0.015	0.103	0.003	120.32	0.38	2.62	0.08
-159	4	3/32	4.987	0.015	0.103	0.003	126.67	0.38	2.62	0.08
-160	5_1/4	3/32	5.237	0.023	0.103	0.003	133.02	0.58	2.62	0.08
-161	5_1/2	3/32	5.487	0.023	0.103	0.003	139.37	0.58	2.62	0.08
-162	5_3/4	3/32	5.737	0.023	0.103	0.003	145.72	0.58	2.62	0.08
-163	6	3/32	5.987	0.023	0.103	0.003	152.07	0.58	2.62	0.08
-164	6_1/4	3/32	6.237	0.023	0.103	0.003	158.42	0.58	2.62	0.08
-165	6_1/2	3/32	6.487	0.023	0.103	0.003	164.77	0.58	2.62	0.08
-166	6_3/4	3/32	6.737	0.023	0.103	0.003	171.12	0.58	2.62	0.08
-167	7	3/32	6.987	0.023	0.103	0.003	177.47	0.58	2.62	0.08
-168	7_1/4	3/32	7.237	0.030	0.103	0.003	183.82	0.76	2.62	0.08
-169	7_1/2	3/32	7.487	0.030	0.103	0.003	190.17	0.76	2.62	0.08
-170	7_3/4	3/32	7.737	0.030	0.103	0.003	196.52	0.76	2.62	0.08
-171	8	3/32	7.987	0.030	0.103	0.003	202.87	0.76	2.62	0.08
-172	8_1/4	3/32	8.237	0.030	0.103	0.003	209.22	0.76	2.62	0.08
-173	8_1/2	3/32	8.487	0.030	0.103	0.003	215.57	0.76	2.62	0.08
-174	8_3/4	3/32	8.737	0.030	0.103	0.003	221.92	0.76	2.62	0.08
-175	9	3/32	8.987	0.030	0.103	0.003	228.27	0.76	2.62	0.08

更多詳細規格資訊，請至耀裕官網查詢 For more information, please visit our website.



AS568 O-RING

STANDARD SIZE LIST SERIES




#AS568	Nominal Size		ACTUAL SIZE								
	Inches 內徑(I.D.)	線徑(W)	Inches 內徑(I.D.) ± 線徑(W) ±				Millimeters 內徑(I.D.) ± 線徑(W) ±				
-176	9_1/4	3/32	9.237	0.030	0.103	0.003	234.62	0.76	2.62	0.08	
-177	9_1/2	3/32	9.487	0.030	0.103	0.003	240.97	0.76	2.62	0.08	
-178	9_3/4	3/32	9.737	0.030	0.103	0.003	247.32	0.76	2.62	0.08	
Size - 179 through - 200 not assigned (尺寸大小179-200未分配)											
-201	3/16	1/8	0.171	0.005	0.139	0.004	4.34	0.12	3.53	0.10	
-202	1/4	1/8	0.234	0.005	0.139	0.004	5.94	0.12	3.53	0.10	
-203	5/16	1/8	0.296	0.005	0.139	0.004	7.52	0.12	3.53	0.10	
-204	3/8	1/8	0.359	0.005	0.139	0.004	9.12	0.12	3.53	0.10	
-205	7/16	1/8	0.421	0.005	0.139	0.004	10.69	0.12	3.53	0.10	
-206	1/2	1/8	0.484	0.005	0.139	0.004	12.29	0.12	3.53	0.10	
-207	9/16	1/8	0.546	0.005	0.139	0.004	13.87	0.12	3.53	0.10	
-208	5/8	1/8	0.609	0.005	0.139	0.004	15.47	0.12	3.53	0.10	
-209	11/16	1/8	0.671	0.005	0.139	0.004	17.04	0.12	3.53	0.10	
-210	3/4	1/8	0.734	0.006	0.139	0.004	18.64	0.15	3.53	0.10	
-211	13/16	1/8	0.796	0.006	0.139	0.004	20.22	0.15	3.53	0.10	
-212	7/8	1/8	0.859	0.006	0.139	0.004	21.82	0.15	3.53	0.10	
-213	15/16	1/8	0.921	0.006	0.139	0.004	23.39	0.15	3.53	0.10	
-214	1	1/8	0.984	0.006	0.139	0.004	25.00	0.15	3.53	0.10	
-215	1_1/16	1/8	1.046	0.006	0.139	0.004	26.57	0.15	3.53	0.10	
-216	1_1/8	1/8	1.109	0.006	0.139	0.004	28.17	0.15	3.53	0.10	
-217	1_3/16	1/8	1.171	0.006	0.139	0.004	29.75	0.15	3.53	0.10	
-218	1_1/4	1/8	1.234	0.006	0.139	0.004	31.34	0.15	3.53	0.10	
-219	1_5/16	1/8	1.296	0.006	0.139	0.004	32.92	0.15	3.53	0.10	
-220	1_3/8	1/8	1.359	0.006	0.139	0.004	34.52	0.15	3.53	0.10	

更多詳細規格資訊，請至耀裕官網查詢 For more information, please visit our website.



AS568 O-RING

STANDARD SIZE LIST SERIES




#AS568	Nominal Size		ACTUAL SIZE							
	Inches 內徑(I.D.)	線徑(W)	Inches 內徑(I.D.) ± 線徑(W) ±				Millimeters 內徑(I.D.) ± 線徑(W) ±			
-221	1_7/16	1/8	1.421	0.006	0.139	0.004	36.10	0.15	3.53	0.10
-222	1_1/2	1/8	1.484	0.006	0.139	0.004	37.70	0.15	3.53	0.10
-223	1_5/8	1/8	1.609	0.010	0.139	0.004	40.87	0.25	3.53	0.10
-224	1_3/4	1/8	1.734	0.010	0.139	0.004	44.05	0.25	3.53	0.10
-225	1_7/8	1/8	1.859	0.010	0.139	0.004	47.22	0.25	3.53	0.10
-226	2	1/8	1.984	0.010	0.139	0.004	50.40	0.25	3.53	0.10
-227	2_1/8	1/8	2.109	0.010	0.139	0.004	53.57	0.25	3.53	0.10
-228	2_1/4	1/8	2.234	0.010	0.139	0.004	56.75	0.25	3.53	0.10
-229	2_3/4	1/8	2.359	0.010	0.139	0.004	59.92	0.25	3.53	0.10
-230	2_1/2	1/8	2.484	0.010	0.139	0.004	63.10	0.25	3.53	0.10
-231	2_5/8	1/8	2.609	0.100	0.139	0.004	66.27	0.25	3.53	0.10
-232	2_3/4	1/8	2.734	0.015	0.139	0.004	69.44	0.38	3.53	0.10
-233	2_7/8	1/8	2.859	0.015	0.139	0.004	72.62	0.38	3.53	0.10
-234	3	1/8	2.984	0.015	0.139	0.004	75.79	0.38	3.53	0.10
-235	3_1/8	1/8	3.109	0.015	0.139	0.004	78.97	0.38	3.53	0.10
-236	3_1/4	1/8	3.234	0.015	0.139	0.004	82.14	0.38	3.53	0.10
-237	3_3/8	1/8	3.359	0.015	0.139	0.004	85.32	0.38	3.53	0.10
-238	3_1/2	1/8	3.484	0.015	0.139	0.004	88.49	0.38	3.53	0.10
-239	3_5/8	1/8	3.609	0.015	0.139	0.004	91.67	0.38	3.53	0.10
-240	3_3/4	1/8	3.734	0.015	0.139	0.004	94.84	0.38	3.53	0.10
-241	3_7/8	1/8	3.859	0.015	0.139	0.004	98.02	0.38	3.53	0.10
-242	4	1/8	3.984	0.015	0.139	0.004	101.19	0.38	3.53	0.10
-243	4_1/8	1/8	4.109	0.015	0.139	0.004	104.37	0.38	3.53	0.10
-244	4_1/4	1/8	4.234	0.015	0.139	0.004	107.54	0.38	3.53	0.10
-245	4_3/8	1/8	4.359	0.015	0.139	0.004	110.72	0.38	3.53	0.10

更多詳細規格資訊，請至耀裕官網查詢 For more information, please visit our website.



AS568 O-RING

STANDARD SIZE LIST SERIES




#AS568	Nominal Size		ACTUAL SIZE							
	Inches	Millimeters	Inches		Millimeters					
	內徑(I.D.)	線徑(W)	內徑(I.D.)	±	線徑(W)	±	內徑(I.D.)	±	線徑(W)	±
-246	4_1/2	1/8	4.484	0.015	0.139	0.004	113.89	0.38	3.53	0.10
-247	4_5/8	1/8	4.609	0.015	0.139	0.004	117.07	0.38	3.53	0.10
-248	4_3/4	1/8	4.734	0.015	0.139	0.004	120.24	0.38	3.53	0.10
-249	4_7/8	1/8	4.859	0.015	0.139	0.004	123.42	0.38	3.53	0.10
-250	5	1/8	4.984	0.015	0.139	0.004	126.59	0.38	3.53	0.10
-251	5_1/8	1/8	5.109	0.023	0.139	0.004	129.77	0.58	3.53	0.10
-252	5_1/4	1/8	5.234	0.023	0.139	0.004	132.94	0.58	3.53	0.10
-253	5_3/8	1/8	5.359	0.023	0.139	0.004	136.12	0.58	3.53	0.10
-254	5_1/2	1/8	5.484	0.023	0.139	0.004	139.30	0.58	3.53	0.10
-255	5_5/8	1/8	5.609	0.023	0.139	0.004	142.47	0.58	3.53	0.10
-256	5_3/4	1/8	5.734	0.023	0.139	0.004	145.65	0.58	3.53	0.10
-257	5_7/8	1/8	5.859	0.023	0.139	0.004	148.82	0.58	3.53	0.10
-258	6	1/8	5.984	0.023	0.139	0.004	152.00	0.58	3.53	0.10
-259	6_1/4	1/8	6.234	0.023	0.139	0.004	158.35	0.58	3.53	0.10
-260	6_1/2	1/8	6.484	0.023	0.139	0.004	164.70	0.58	3.53	0.10
-261	6_3/4	1/8	6.734	0.023	0.139	0.004	171.05	0.58	3.53	0.10
-262	7	1/8	6.984	0.023	0.139	0.004	177.40	0.58	3.53	0.10
-263	7_1/4	1/8	7.234	0.030	0.139	0.004	183.75	0.76	3.53	0.10
-264	7_1/2	1/8	7.484	0.030	0.139	0.004	190.10	0.76	3.53	0.10
-265	7_3/4	1/8	7.734	0.030	0.139	0.004	196.45	0.76	3.53	0.10
-266	8	1/8	7.984	0.030	0.139	0.004	202.80	0.76	3.53	0.10
-267	8_1/4	1/8	8.234	0.030	0.139	0.004	209.15	0.76	3.53	0.10
-268	8_1/2	1/8	8.484	0.030	0.139	0.004	215.50	0.76	3.53	0.10

更多詳細規格資訊，請至耀裕官網查詢 For more information, please visit our website.



AS568 O-RING

STANDARD SIZE LIST SERIES




#AS568	Nominal Size		ACTUAL SIZE								
	Inches 內徑(I.D.)	線徑(W)	Inches 內徑(I.D.) ± 線徑(W) ±				Millimeters 內徑(I.D.) ± 線徑(W) ±				
-269	8_3/4	1/8	8.734	0.030	0.139	0.004	221.85	0.76	3.53	0.10	
-270	9	1/8	8.984	0.030	0.139	0.004	228.20	0.76	3.53	0.10	
-271	9_1/4	1/8	9.234	0.030	0.139	0.004	234.55	0.76	3.53	0.10	
-272	9_1/2	1/8	9.484	0.030	0.139	0.004	240.90	0.76	3.53	0.10	
-273	9_3/4	1/8	9.734	0.030	0.139	0.004	247.25	0.76	3.53	0.10	
-274	10	1/8	9.984	0.030	0.139	0.004	253.60	0.76	3.53	0.10	
-275	10_1/2	1/8	10.484	0.030	0.139	0.004	266.30	0.76	3.53	0.10	
-276	11	1/8	10.984	0.030	0.139	0.004	279.00	0.76	3.53	0.10	
-277	11_1/2	1/8	11.484	0.030	0.139	0.004	291.70	0.76	3.53	0.10	
-278	12	1/8	11.984	0.030	0.139	0.004	304.40	0.76	3.53	0.10	
-279	13	1/8	12.984	0.030	0.139	0.004	329.80	0.76	3.53	0.10	
-280	14	1/8	13.984	0.030	0.139	0.004	355.20	0.76	3.53	0.10	
-281	15	1/8	14.984	0.030	0.139	0.004	380.60	0.76	3.53	0.10	
-282	16	1/8	15.955	0.045	0.139	0.004	405.26	1.14	3.53	0.10	
-283	17	1/8	16.955	0.045	0.139	0.004	430.66	1.14	3.53	0.10	
-284	18	1/8	17.955	0.045	0.139	0.004	456.06	1.14	3.53	0.10	
Size - 285 through - 308 not assigned (尺寸大小285-308未分配)											
-309	7/16	3/16	0.412	0.005	0.210	0.005	10.46	0.12	5.34	0.12	
-310	1/2	3/16	0.475	0.005	0.210	0.005	12.07	0.12	5.34	0.12	
-311	9/16	3/16	0.537	0.005	0.210	0.005	13.64	0.12	5.34	0.12	
-312	5/8	3/16	0.600	0.005	0.210	0.005	15.24	0.12	5.34	0.12	
-313	11/16	3/16	0.662	0.005	0.210	0.005	16.81	0.12	5.34	0.12	
-314	3/4	3/16	0.725	0.006	0.210	0.005	18.42	0.15	5.34	0.12	
-315	13/16	3/16	0.787	0.006	0.210	0.005	19.99	0.15	5.34	0.12	
-316	7/8	3/16	0.850	0.006	0.210	0.005	21.59	0.15	5.34	0.12	

更多詳細規格資訊，請至耀裕官網查詢 For more information, please visit our website.



AS568 O-RING

STANDARD SIZE LIST SERIES




#AS568	Nominal Size		ACTUAL SIZE							
	Inches 內徑(I.D.)	線徑(W)	Inches 內徑(I.D.) ± 線徑(W) ±				Millimeters 內徑(I.D.) ± 線徑(W) ±			
-317	15/16	3/16	0.912	0.006	0.210	0.005	23.16	0.15	5.34	0.12
-318	1	3/16	0.975	0.006	0.210	0.005	24.77	0.15	5.34	0.12
-319	1_1/16	3/16	1.037	0.006	0.210	0.005	26.34	0.15	5.34	0.12
-320	1_1/8	3/16	1.100	0.006	0.210	0.005	27.94	0.15	5.34	0.12
-321	1_3/16	3/16	1.162	0.006	0.210	0.005	29.51	0.15	5.34	0.12
-322	1_1/4	3/16	1.225	0.006	0.210	0.005	31.12	0.15	5.34	0.12
-323	1_5/16	3/16	1.287	0.006	0.210	0.005	32.69	0.15	5.34	0.12
-324	1_3/8	3/16	1.350	0.006	0.210	0.005	34.29	0.15	5.34	0.12
-325	1_1/2	3/16	1.475	0.010	0.210	0.005	37.47	0.25	5.34	0.12
-326	1_5/8	3/16	1.600	0.010	0.210	0.005	40.65	0.25	5.34	0.12
-327	1_3/4	3/16	1.725	0.010	0.210	0.005	43.82	0.25	5.34	0.12
-328	1_7/8	3/16	1.850	0.010	0.210	0.005	46.99	0.25	5.34	0.12
-329	2	3/16	1.975	0.010	0.210	0.005	50.16	0.25	5.34	0.12
-330	2_1/8	3/16	2.100	0.010	0.210	0.005	53.34	0.25	5.34	0.12
-331	2_1/4	3/16	2.225	0.010	0.210	0.005	56.52	0.25	5.34	0.12
-332	2_3/8	3/16	2.350	0.010	0.210	0.005	59.69	0.25	5.34	0.12
-333	2_1/2	3/16	2.475	0.010	0.210	0.005	62.87	0.25	5.34	0.12
-334	2_5/8	3/16	2.600	0.010	0.210	0.005	66.04	0.25	5.34	0.12
-335	2_3/4	3/16	2.725	0.015	0.210	0.005	69.22	0.38	5.34	0.12
-336	2_7/8	3/16	2.850	0.015	0.210	0.005	72.39	0.38	5.34	0.12
-337	3	3/16	2.975	0.015	0.210	0.005	75.57	0.38	5.34	0.12
-338	3_1/8	3/16	3.100	0.015	0.210	0.005	78.74	0.38	5.34	0.12
-339	3_1/4	3/16	3.225	0.015	0.210	0.005	81.92	0.38	5.34	0.12

更多詳細規格資訊，請至耀裕官網查詢 For more information, please visit our website.



AS568 O-RING

STANDARD SIZE LIST SERIES




#AS568	Nominal Size		ACTUAL SIZE							
	Inches 內徑(I.D.)	線徑(W)	Inches 內徑(I.D.) ± 線徑(W) ±				Millimeters 內徑(I.D.) ± 線徑(W) ±			
-340	3_3/8	3/16	3.350	0.015	0.210	0.005	85.09	0.38	5.34	0.12
-341	3_1/2	3/16	3.475	0.015	0.210	0.005	88.27	0.38	5.34	0.12
-342	3_5/8	3/16	3.600	0.015	0.210	0.005	91.44	0.38	5.34	0.12
-343	3_3/4	3/16	3.725	0.015	0.210	0.005	94.62	0.38	5.34	0.12
-344	3_7/8	3/16	3.850	0.015	0.210	0.005	97.79	0.38	5.34	0.12
-345	4	3/16	3.975	0.015	0.210	0.005	100.96	0.38	5.34	0.12
-346	4_1/8	3/16	4.100	0.015	0.210	0.005	104.14	0.38	5.34	0.12
-347	4_1/4	3/16	4.225	0.015	0.210	0.005	107.32	0.38	5.34	0.12
-348	4_3/8	3/16	4.35	0.015	0.210	0.005	110.49	0.38	5.34	0.12
-349	4_1/2	3/16	4.475	0.015	0.210	0.005	113.67	0.38	5.34	0.12
-350	4_5/8	3/16	4.600	0.015	0.210	0.005	116.84	0.38	5.34	0.12
-351	4_3/4	3/16	4.725	0.015	0.210	0.005	120.02	0.38	5.34	0.12
-352	4_7/8	3/16	4.850	0.015	0.210	0.005	123.19	0.38	5.34	0.12
-353	5	3/16	4.975	0.015	0.210	0.005	126.37	0.38	5.34	0.12
-354	5_1/8	3/16	5.100	0.023	0.210	0.005	129.54	0.58	5.34	0.12
-355	5_1/4	3/16	5.225	0.023	0.210	0.005	132.72	0.58	5.34	0.12
-356	5_3/8	3/16	5.35	0.023	0.210	0.005	135.89	0.58	5.34	0.12
-357	5_1/2	3/16	5.475	0.023	0.210	0.005	139.307	0.58	5.34	0.12
-358	5_5/8	3/16	5.600	0.023	0.210	0.005	142.24	0.58	5.34	0.12
-359	5_3/4	3/16	5.725	0.023	0.210	0.005	145.42	0.58	5.34	0.12
-360	5_7/8	3/16	5.850	0.023	0.210	0.005	148.59	0.58	5.34	0.12
-361	6	3/16	5.975	0.023	0.210	0.005	151.77	0.58	5.34	0.12
-362	6_1/4	3/16	6.225	0.023	0.210	0.005	158.12	0.58	5.34	0.12
-363	6_1/2	3/16	6.475	0.023	0.210	0.005	164.47	0.58	5.34	0.12
-364	6_3/4	3/16	6.725	0.023	0.210	0.005	170.82	0.58	5.34	0.12

更多詳細規格資訊，請至耀裕官網查詢 For more information, please visit our website.



AS568 O-RING

STANDARD SIZE LIST SERIES




#AS568	Nominal Size	ACTUAL SIZE								
		Inches		Inches		Millimeters				
內徑(I.D.)	線徑(W)	內徑(I.D.)	±	線徑(W)	±	內徑(I.D.)	±	線徑(W)	±	
-365	7	3/16	6.975	0.023	0.210	0.005	177.17	0.58	5.34	0.12
-366	7_1/4	3/16	7.225	0.030	0.210	0.005	183.52	0.76	5.34	0.12
-367	7_1/2	3/16	7.475	0.030	0.210	0.005	189.87	0.76	5.34	0.12
-368	7_3/4	3/16	7.725	0.030	0.210	0.005	196.22	0.76	5.34	0.12
-369	8	3/16	7.975	0.030	0.210	0.005	202.57	0.76	5.34	0.12
-370	8_1/4	3/16	8.225	0.030	0.210	0.005	208.92	0.76	5.34	0.12
-371	8_1/2	3/16	8.475	0.030	0.210	0.005	215.27	0.76	5.34	0.12
-372	8_3/4	3/16	8.725	0.030	0.210	0.005	221.62	0.76	5.34	0.12
-373	9	3/16	8.975	0.030	0.210	0.005	227.97	0.76	5.34	0.12
-374	9_1/4	3/16	9.225	0.030	0.210	0.005	234.32	0.76	5.34	0.12
-375	9_1/2	3/16	9.475	0.030	0.210	0.005	240.67	0.76	5.34	0.12
-376	9_3/4	3/16	9.725	0.030	0.210	0.005	247.02	0.76	5.34	0.12
-377	10	3/16	9.975	0.030	0.210	0.005	253.37	0.76	5.34	0.12
-378	10_1/2	3/16	10.475	0.030	0.210	0.005	266.07	0.76	5.34	0.12
-379	11	3/16	10.975	0.030	0.210	0.005	278.77	0.76	5.34	0.12
-380	11_1/2	3/16	11.475	0.030	0.210	0.005	291.47	0.76	5.34	0.12
-381	12	3/16	11.975	0.030	0.210	0.005	304.17	0.76	5.34	0.12
-382	13	3/16	12.975	0.030	0.210	0.005	329.57	0.76	5.34	0.12
-383	14	3/16	13.975	0.030	0.210	0.005	354.97	0.76	5.34	0.12
-384	15	3/16	14.975	0.030	0.210	0.005	380.37	0.76	5.34	0.12
-385	16	3/16	15.955	0.045	0.210	0.005	405.26	1.14	5.34	0.12
-386	17	3/16	16.955	0.045	0.210	0.005	430.66	1.14	5.34	0.12
-387	18	3/16	17.955	0.045	0.210	0.005	456.06	1.14	5.34	0.12



AS568 O-RING

STANDARD SIZE LIST SERIES




#AS568	Nominal Size		ACTUAL SIZE								
	Inches 內徑(I.D.)	線徑(W)	Inches 內徑(I.D.) ± 線徑(W) ±				Millimeters 內徑(I.D.) ± 線徑(W) ±				
-388	19	3/16	18.955	0.045	0.210	0.005	481.46	1.14	5.34	0.12	
-389	20	3/16	19.955	0.045	0.210	0.005	506.86	1.14	5.34	0.12	
-390	21	3/16	20.955	0.045	0.210	0.005	532.25	1.14	5.34	0.12	
-391	22	3/16	21.955	0.045	0.210	0.005	557.66	1.14	5.34	0.12	
-392	23	3/16	22.940	0.060	0.210	0.005	582.7	1.50	5.34	0.12	
-393	24	3/16	23.940	0.060	0.210	0.005	608.1	1.50	5.34	0.12	
-394	25	3/16	24.940	0.060	0.210	0.005	633.5	1.50	5.34	0.12	
-395	26	3/16	25.940	0.060	0.210	0.005	658.9	1.50	5.34	0.12	
Size - 396 through - 424 not assigned (尺寸大小396-424未分配)											
-425	4_1/2	1/4	4.475	0.015	0.275	0.006	113.67	0.38	6.99	0.15	
-426	4_5/8	1/4	4.600	0.015	0.275	0.006	116.84	0.38	6.99	0.15	
-427	4_3/4	1/4	4.725	0.015	0.275	0.006	120.02	0.38	6.99	0.15	
-428	4_7/8	1/4	4.850	0.015	0.275	0.006	123.19	0.38	6.99	0.15	
-429	5	1/4	4.975	0.015	0.275	0.006	126.37	0.38	6.99	0.15	
-430	5_1/8	1/4	5.100	0.023	0.275	0.006	129.54	0.58	6.99	0.15	
-431	5_1/4	1/4	5.225	0.023	0.275	0.006	132.72	0.58	6.99	0.15	
-432	5_3/8	1/4	5.350	0.023	0.275	0.006	135.89	0.58	6.99	0.15	
-433	5_1/2	1/4	5.475	0.023	0.275	0.006	139.07	0.58	6.99	0.15	
-434	5_5/8	1/4	5.600	0.023	0.275	0.006	142.24	0.58	6.99	0.15	
-435	5_3/4	1/4	5.725	0.023	0.275	0.006	145.42	0.58	6.99	0.15	
-436	5_7/8	1/4	5.850	0.023	0.275	0.006	148.59	0.58	6.99	0.15	
-437	6	1/4	5.975	0.023	0.275	0.006	151.77	0.58	6.99	0.15	
-438	6_1/4	1/4	6.225	0.023	0.275	0.006	158.12	0.58	6.99	0.15	
-439	6_1/2	1/4	6.475	0.023	0.275	0.006	164.47	0.58	6.99	0.15	
-440	6_3/4	1/4	7.725	0.023	0.275	0.006	170.82	0.58	6.99	0.15	

更多詳細規格資訊，請至耀裕官網查詢 For more information, please visit our website.



AS568 O-RING

STANDARD SIZE LIST SERIES




#AS568	Nominal Size		ACTUAL SIZE							
	Inches	內徑(I.D.) 線徑(W)	Inches				Millimeters			
		內徑(I.D.)	±	線徑(W)	±	內徑(I.D.)	±	線徑(W)	±	
-441	7	1/4	6.975	0.023	0.275	0.006	177.17	0.58	6.99	0.15
-442	7_1/4	1/4	7.225	0.030	0.275	0.006	183.52	0.76	6.99	0.15
-443	7_1/2	1/4	7.475	0.030	0.275	0.006	189.87	0.76	6.99	0.15
-444	7_3/4	1/4	7.725	0.030	0.275	0.006	196.22	0.76	6.99	0.15
-445	8	1/4	7.975	0.030	0.275	0.006	202.57	0.76	6.99	0.15
-446	8_1/2	1/4	8.475	0.030	0.275	0.006	215.27	0.76	6.99	0.15
-447	9	1/4	8.975	0.030	0.275	0.006	227.97	0.76	6.99	0.15
-448	9_1/2	1/4	9.475	0.030	0.275	0.006	240.67	0.76	6.99	0.15
-449	10	1/4	9.975	0.030	0.275	0.006	253.37	0.76	6.99	0.15
-450	10_1/2	1/4	10.475	0.030	0.275	0.006	266.07	0.76	6.99	0.15
-451	11	1/4	10.975	0.030	0.275	0.006	278.77	0.76	6.99	0.15
-452	11_1/2	1/4	11.475	0.030	0.275	0.006	291.47	0.76	6.99	0.15
-453	12	1/4	11.975	0.030	0.275	0.006	304.17	0.76	6.99	0.15
-454	12_1/2	1/4	12.475	0.030	0.275	0.006	316.87	0.76	6.99	0.15
-455	13	1/4	12.975	0.030	0.275	0.006	329.57	0.76	6.99	0.15
-456	13_1/2	1/4	13.475	0.030	0.275	0.006	342.27	0.76	6.99	0.15
-457	14	1/4	13.975	0.030	0.275	0.006	354.97	0.76	6.99	0.15
-458	14_1/2	1/4	14.475	0.030	0.275	0.006	367.67	0.76	6.99	0.15
-459	15	1/4	14.975	0.030	0.275	0.006	380.37	0.76	6.99	0.15
-460	15_1/2	1/4	15.475	0.030	0.275	0.006	393.08	0.76	6.99	0.15
-461	16	1/4	15.955	0.045	0.275	0.006	405.26	1.14	6.99	0.15
-462	16_1/2	1/4	16.455	0.045	0.275	0.006	417.96	1.14	6.99	0.15
-463	17	1/4	16.955	0.045	0.275	0.006	430.66	1.14	6.99	0.15

更多詳細規格資訊，請至耀裕官網查詢 For more information, please visit our website.



AS568 O-RING

STANDARD SIZE LIST SERIES




#AS568	Nominal Size		ACTUAL SIZE								
	Inches 內徑(I.D.)	線徑(W)	Inches 內徑(I.D.) ± 線徑(W) ±				Millimeters 內徑(I.D.) ± 線徑(W) ±				
-464	17_1/2	1/4	17.455	0.045	0.275	0.006	443.36	1.14	6.99	0.15	
-465	18	1/4	17.955	0.045	0.275	0.006	456.06	1.14	6.99	0.15	
-466	18_1/2	1/4	18.455	0.045	0.275	0.006	468.76	1.14	6.99	0.15	
-467	19	1/4	18.955	0.045	0.275	0.006	481.46	1.14	6.99	0.15	
-468	19_1/2	1/4	19.455	0.045	0.275	0.006	494.16	1.14	6.99	0.15	
-469	20	1/4	19.955	0.045	0.275	0.006	506.86	1.14	6.99	0.15	
-470	21	1/4	20.955	0.045	0.275	0.006	532.26	1.14	6.99	0.15	
-471	22	1/4	21.955	0.045	0.275	0.006	557.66	1.14	6.99	0.15	
-472	23	1/4	22.940	0.060	0.275	0.006	582.70	1.50	6.99	0.15	
-473	24	1/4	23.940	0.060	0.275	0.006	608.10	1.50	6.99	0.15	
-474	25	1/4	24.940	0.060	0.275	0.006	633.50	1.50	6.99	0.15	
-475	26	1/4	25.940	0.060	0.275	0.006	658.90	1.50	6.99	0.15	
Size - 475 through - 901 not assigned (尺寸大小475-901未分配)											
-901	3/32	1/4	0.185	0.005	0.056	0.003	4.70	0.12	1.42	0.08	
-902	1/8	1/4	0.239	0.005	0.064	0.003	6.07	0.12	1.63	0.08	
-903	3/16	1/4	0.301	0.005	0.064	0.003	7.65	0.12	1.63	0.08	
-904	1/4	1/4	0.351	0.005	0.072	0.003	8.92	0.12	1.83	0.08	
-905	5/16	1/4	0.414	0.005	0.072	0.003	10.52	0.12	1.83	0.08	
-906	3/8	1/4	0.468	0.005	0.078	0.003	11.89	0.12	1.98	0.08	
-907	7/16	1/4	0.530	0.005	0.082	0.003	13.47	0.12	2.08	0.08	
-908	1/2	1/4	0.644	0.005	0.087	0.003	16.36	0.12	2.21	0.08	
-909	9/16	1/4	0.706	0.005	0.097	0.003	17.94	0.12	2.46	0.08	
-910	5/8	1/4	0.755	0.005	0.097	0.003	19.18	0.12	2.46	0.08	
-911	11/16	1/4	0.863	0.005	0.116	0.004	21.92	0.15	2.95	0.10	
-912	3/4	1/4	0.924	0.006	0.116	0.004	23.47	0.15	2.95	0.10	

更多詳細規格資訊，請至耀裕官網查詢 For more information, please visit our website.



AS568 O-RING

STANDARD SIZE LIST SERIES



#AS568	Nominal Size		ACTUAL SIZE							
	Inches		Inches				Millimeters			
		內徑(I.D.)	線徑(W)	±	內徑(I.D.)	線徑(W)	±	內徑(I.D.)	線徑(W)	±
-913	13/16	1/4	0.986	0.006	0.116	0.004	25.04	0.15	2.95	0.10
-914	7/8	1/4	1.047	0.006	0.116	0.004	26.60	0.15	2.95	0.10
-916	1	1/4	1.171	0.006	0.116	0.004	29.75	0.15	2.95	0.10
-918	1_1/8	1/4	1.355	0.006	0.116	0.004	34.42	0.15	2.95	0.10
-920	1_1/4	1/4	1.475	0.010	0.118	0.004	37.46	0.25	2.95	0.10
-924	1_1/2	1/4	1.720	0.010	0.118	0.004	43.68	0.25	3	0.10
-928	1_3/4	1/4	2.09	0.010	0.118	0.004	53.09	0.25	3	0.10
-932	2	1/4	2.337	0.010	0.118	0.004	59.36	0.25	3	0.10



耀裕橡膠有限公司
YAW-YEW RUBBER CO., LTD.

- 彰化縣福興鄉番社村番社街49之8號
No.49-8, Fanshe St., Fuxing Township, Changhua County 506, Taiwan (R.O.C)
- +886-4-7783390
- +886-4-7782764
- Mail y7783390@ms33.hinet.net
- <http://www.yaw-yew.com.tw>



更多耀裕訊息即刻上網



更多NSF資訊即刻上網